



PCMCIA CARD SPECIFICATIONS	
Part Number:	A59944
Interface:	4 x External eSATA Ports, 133MHz / 64 bit PCI-X
Interface Transfer Rate:	3GB/s SATA II Gen 2
Slot Compliance:	PCI-X Addendum 1.0a, PCI Local Bus Specification 2.3, PCI Hot Plug Specification
Digital Video:	Full Support
SATA Compliance:	Serial ATA 1.0a, Serial ATA II Extensions to Serial ATA 1.0, Serial ATA Gen2 PHY Specification Port Multiplier Specification 1.1, External Serial ATA Connector (SATA II Cables & Connectors Vol 1)
Power Requirement:	2.0 amps @ +3.3V
Protocols :	Function Control Protocol (FCP) Connection Management Protocol (CMP)
Operating Systems:	Win Server 2003, Win 2000, XP Pro, Vista Mac OS 10.3.9 or Later
System Requirements:	Intel PC, Apple Mac or equivalent Available Universal PCI or PCI-X Slot
Dimensions:	6.5" (L) X 4.25" (W)
Warranty:	1 Year

## EZQuest eSATA PCI-X Card

The EZQuest eSATA PCI-X Card is designed to maximize the performance of the EZQuest SteelVine RAID as well as other storage solution requiring host-side external SATA support.

The card features 4 ports that deliver throughput up to 3GB/s through each port. The EZQuest eSATA PCI-X Card also supports advanced SATA II features such as native command queuing, port multipliers with FIS-based switching, and adjustable signal strength up to 2 meters.

They are designed for high performance by using on-chip memory and command-state machines of the controller to minimize command latency and host CPU utilization.

## EZQuest, Inc.

1051 North Shepard Street  
Anheim, CA 92806

Phone: 714.666.1716

Fax: 714.666.8861

Copyright© 2005 EZQuest, Inc. All rights reserved.

[www.ezq.com](http://www.ezq.com)