



PCMCIA CARD SPECIFICATIONS	
Part Number:	A59922
Interface:	2 x External eSATA Ports, 133MHz / 64bit PCI-X
Interface Transfer Rate:	1.5GB/s SATA I
Slot Compliance:	PCI-X Addendum 1.0a, PCI Local Bus Specification 1.3, PCI Hot Plug Spec. 1.0
Digital Video:	Full Support
SATA Compliance:	Serial ATA 1.0a, Serial ATA II Extensions to Serial ATA 1.0, Serial ATA Gen1 PHY Specification Port Multiplier Specification 1.1, External Serial ATA Connector (SATA II Cables & Connectors Vol 1)
Included Software:	Driver for Mac and PC
Protocols :	Function Control Protocol (FCP) Connection Management Protocol (CMP)
Operating Systems:	Win Server 2003, Win 2000, XP Pro, Vista Mac OS 10.4.1 or Later
System Requirements:	Intel PC, Apple Mac or equivalent Available Universal PCI or PCI-Exps Slot
Dimensions:	4.73" (L) X 3.39" (W)
Warranty:	1 Year

EZQuest 2 Port eSATA II PCI Express Card

The EZQuest eSATA PCI-Express Card is designed to maximize the performance of the EZQuest SteelVine RAID as well as other storage solution requiring host-side external SATA support. The card features 2 ports that deliver throughput up to 2.5GB/s through each port. The EZQuest eSATA PCI-Express Card also supports advanced SATA II features such as native command queuing, port multipliers with FIS-based switching, and adjustable signal strength up to 2 meters. They are designed for high performance by using on-chip memory and command-state machines of the controller to minimize command latency and host CPU utilization.

EZQuest, Inc.

1051 North Shepard Street
Anheim, CA 92806

Phone: 714.666.1716

Fax: 714.666.8861

Copyright© 2005 EZQuest, Inc. All rights reserved.

www.ezq.com